

**ABSTRACT:**

In a hand mixer (1) having two mains terminals (10, 11) and having interference suppression means (16) for a motor (27) and having a switching means configuration (130) which includes speed switching means (60) for switching the speed of the motor (27) to different lower speed values and start means (61) for starting the motor (27) at a higher speed, the two mains terminals (10, 11) and the speed switching means (60) and the start means (61) and preferably also the interference suppression means are connected mechanically and electrically to form a module (9), all the electrical connections between said parts of the module (9) being realized on the module (9).

10 (Fig. 10)

Fitted by sex		Fitted by age		Fitted by sex and age	
Age	Sex	Age	Sex	Age	Sex
1	1	1	1	1	1
2	1	2	1	2	1
3	1	3	1	3	1
4	1	4	1	4	1
5	1	5	1	5	1
6	1	6	1	6	1
7	1	7	1	7	1
8	1	8	1	8	1
9	1	9	1	9	1
10	1	10	1	10	1
11	1	11	1	11	1
12	1	12	1	12	1
13	1	13	1	13	1
14	1	14	1	14	1
15	1	15	1	15	1
16	1	16	1	16	1
17	1	17	1	17	1
18	1	18	1	18	1
19	1	19	1	19	1
20	1	20	1	20	1
21	1	21	1	21	1
22	1	22	1	22	1
23	1	23	1	23	1
24	1	24	1	24	1
25	1	25	1	25	1
26	1	26	1	26	1
27	1	27	1	27	1
28	1	28	1	28	1
29	1	29	1	29	1
30	1	30	1	30	1
31	1	31	1	31	1
32	1	32	1	32	1
33	1	33	1	33	1
34	1	34	1	34	1
35	1	35	1	35	1
36	1	36	1	36	1
37	1	37	1	37	1
38	1	38	1	38	1
39	1	39	1	39	1
40	1	40	1	40	1
41	1	41	1	41	1
42	1	42	1	42	1
43	1	43	1	43	1
44	1	44	1	44	1
45	1	45	1	45	1
46	1	46	1	46	1
47	1	47	1	47	1
48	1	48	1	48	1
49	1	49	1	49	1
50	1	50	1	50	1
51	1	51	1	51	1
52	1	52	1	52	1
53	1	53	1	53	1
54	1	54	1	54	1
55	1	55	1	55	1
56	1	56	1	56	1
57	1	57	1	57	1
58	1	58	1	58	1
59	1	59	1	59	1
60	1	60	1	60	1
61	1	61	1	61	1
62	1	62	1	62	1
63	1	63	1	63	1
64	1	64	1	64	1
65	1	65	1	65	1
66	1	66	1	66	1
67	1	67	1	67	1
68	1	68	1	68	1
69	1	69	1	69	1
70	1	70	1	70	1
71	1	71	1	71	1
72	1	72	1	72	1
73	1	73	1	73	1
74	1	74	1	74	1
75	1	75	1	75	1
76	1	76	1	76	1
77	1	77	1	77	1
7					